

## LED LINEAR PROFILE

L-LCL-9086



Slim elegant and powerful linear profile. The 9086 can be installed recessed, surface or suspended. With the connection kit and the magnetic end caps, you can connect several pieces to address your architectural needs.

*Le Linéaire 9086 est un profilé élégant et puissant. Il s'installe en saillie, suspension ou encastré. Grâce au kit de connexion et embouts magnétiques, il se connecte et permet de créer des lignes continues de grande longueur sans perte de flux ni d'uniformité.*

AC Input	100 – 277 V	<i>Alimentation</i>
Light Source	SMD	<i>Source</i>
Wattage	35W/m	<i>Puissance</i>
Lumen Output	4100Lm/m	<i>Flux lumineux</i>
Efficiency	117Lm/W	<i>Efficacité</i>
Beam Angle	98°	<i>Angles</i>
Color (K)	3000°K   4000°K   6000°K	<i>Température</i>
Finish	Silver   White   Black	<i>Finition</i>
Working Temperature	-20° / +45°C	<i>Température de fonctionnement</i>
Lifetime	50,000h	<i>Durée de vie</i>
Standard	L80B10	<i>Norme</i>
Protection	IP40	<i>Indice</i>

Dimming (Option)	1-10V   DALI   Phase dimming	<i>Contrôle (Option)</i>
Certification	CE   RoHS	<i>Certification</i>
CRI	80+   90+	<i>IRC</i>
Safety Class		<i>Classe de sécurité</i>
EN62471	RG0	<i>EN62471</i>
SDCM	<3	<i>SDCM</i>
UGR	≤19	<i>UGR</i>

## Product Photo | *Photo du produit*





# LUMEN

AT WORK



[contact@lumen-at-work.com](mailto:contact@lumen-at-work.com) | [www.lumen-at-work.com](http://www.lumen-at-work.com)

© LUMEN AT WORK. All rights reserved. The information provided herein is subject to change, without notice.